

Bill Jennings
California Sportfishing Protection Alliance
3536 Rainier Avenue
Stockton, CA 95204
Tel: 209-464-5067
Fax: 209-464-1028
E-mail: deltakeep@aol.com

Mike Jackson
Law Office of Mike Jackson
P.O. Box 207
429 W. Main Street
Quincy, CA 95971
Tel: 530-283-1007
Fax: 530-283-0712
E-mail: mjatty@sbcglobal.net

VIA: Electronic Submission
Hardcopy to Follow

Andrew Packard
Law Office of Andrew Packard
319 Pleasant Street
Petaluma, CA 94952
Tel: 707-763-7227
Fax: 707-763-9227
E-mail: andrew@packardlawoffices.com

For Petitioner California Sportfishing Protection Alliance

BEFORE THE STATE WATER RESOURCES CONTROL BOARD

In the Matter of Waste Discharge Requirements For)	
Tuolumne Utilities District Sonora Regional)	PETITION FOR REVIEW
Wastewater Treatment Plant and Jamestown)	
Sanitary District Jamestown Wastewater Treatment)	
Plant; California Regional Water Quality Control)	
Board – Central Valley Region Order No. R5-2008-)	
0162; NPDES No. CA0084727)	

Pursuant to Section 13320 of California Water Code and Section 2050 of Title 23 of the California Code of Regulations (CCR), California Sportfishing Protection Alliance (“CSPA” or “petitioner”) petitions the State Water Resources Control Board (State Board) to review and vacate the final decision of the California Regional Water Quality Control Board for the Central Valley Region (“Regional Board”) in adopting Waste Discharge Requirements (NPDES No. CA0084727) for Tuolumne Utilities District Sonora Regional Wastewater Treatment Plant and Jamestown Sanitary District

Jamestown Wastewater Treatment Plant, on 24 October 2008. *See* Order No. R5-2008-0162. The issues raised in this petition were raised in timely written comments.

1. NAME AND ADDRESS OF THE PETITIONERS:

California Sportfishing Protection Alliance
3536 Rainier Avenue
Stockton, California 95204
Attention: Bill Jennings, Executive Director

2. THE SPECIFIC ACTION OR INACTION OF THE REGIONAL BOARD WHICH THE STATE BOARD IS REQUESTED TO REVIEW AND A COPY OF ANY ORDER OR RESOLUTION OF THE REGIONAL BOARD WHICH IS REFERRED TO IN THE PETITION:

Petitioner seeks review of Order No. R5-2008-0162, Waste Discharge Requirements (NPDES No. CA0084727) for the Tuolumne Utilities District Sonora Regional Wastewater Treatment Plant and Jamestown Sanitary District Jamestown Wastewater Treatment Plant. A copy of the adopted Order is attached as Attachment No.

1.

3. THE DATE ON WHICH THE REGIONAL BOARD ACTED OR REFUSED TO ACT OR ON WHICH THE REGIONAL BOARD WAS REQUESTED TO ACT:

24 October 2008

4. A FULL AND COMPLETE STATEMENT OF THE REASONS THE ACTION OR FAILURE TO ACT WAS INAPPROPRIATE OR IMPROPER:

CSPA submitted a detailed comment letter on 16 September 2008. That letter and the following comments set forth in detail the reasons and points and authorities why CSPA believes the Order fails to comport with statutory and regulatory requirements. The specific reasons the adopted Orders are improper are:

The Tuolumne Utilities District (TUD), Sonora Regional Wastewater Treatment Plant, provides secondary treatment and discharges during wet weather under twenty to one dilution conditions to Woods Creek tributary to New Don Pedro Reservoir. During dry weather secondary treated wastewater is reclaimed for fodder crop irrigation. Waste/Reclaimed water is stored in Quartz Reservoir (1,500 acre feet) prior to irrigation or discharge to surface waters.

The Permit only addresses the surface water discharge and land disposal, via storage (percolation/evaporation) and irrigation is regulated under separate Waste Discharge Requirements (WDRs) Order No. R5-2002-0202. The WDRs show that:

- many reclaimed water storage ponds were within surface water drainage courses;
- runoff had been documented at the end of the land application areas;
- aerial inspections revealed overspray and runoff from the irrigation areas;
- prior to issuance of the NPDES permit there were numerous discharges of wastewater to surface waters from Quartz Reservoir;
- the soil mantel in the area is thin, approximately less than 5 inches;
- the thin soil mantel overlies fractured bedrock;
- groundwater is utilized for domestic and irrigation uses pumped from wells within the fractured bedrock;
- Quartz Reservoir is partially lined and has been shown to percolate up to 258,600 gallons per day.

The WDRs are not currently being considered for renewal. We are generally not opposed to regulating single sites under separate Orders corresponding to the Regional Board's various programs. However, because of issues related to illegal wastewater discharges to surface waters, groundwater degradation including the threat to human health, compliance with the Antidegradation Policy and providing best practicable treatment and control (BPTC) of the discharge we requested that a WDR renewal be considered by the Regional Board at the same hearing for consideration of the proposed NPDES Permit. It is impossible to separate the disposal practices of this wastewater treatment plant when considering whether the facility provides BPTC and therefore complies with the Antidegradation Policy.

It also appears at best odd the for the NPDES discharge; treated and disinfected wastewater is placed in a storage reservoir possibly for several months prior to discharge and is capable of complying with Effluent Limitations based on secondary treatment for coliform organisms, BOD and TSS. The pond does not appear to be protected from birds and wildlife and there does not appear to be a means of limiting algae growth. The Regional Board failed to address these concerns in considering the NPDES Permit. It is requested that the State Board consider under its own authority or require the Regional Board to consider all the impacts of the wastewater discharge within one action.

Our points and authorities regarding the Permit are as follows:

- A. The Permit allows for mixing zones for chloroform (cancer potency factor), manganese and nitrate and nitrite in violation of the requirements of the Central Valley Regional Water Quality Control Board's Basin Plan, page IV-16.00, which requires the Regional Board use EPA's *Technical Support Document for Water Quality Based Toxics Control (TSD)* in assessing mixing zones and the State's *Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays and Estuaries of California (SIP)*, Section 1.4.2.2, which contains extensive requirements for a mixing zone study which must be analyzed before a mixing zone is allowed for a wastewater discharge.**

A “completely mixed discharge” is defined by the SIP, Appendix 1-1, when a pollutant concentration is less than 5% different across a transect of the waterbody at a point within two stream/river widths from the point of discharge. The SIP, Section 1.4.2, requires that for incompletely mixed discharges; mixing zones will only be considered following the completion of a mixing zone study by the Discharger. The Permit, page F-14, contains the following statements regarding mixing of the discharge with receiving waters:

- For human health criteria: “For human health criteria it is a valid assumption that the discharge is completely mixed with the receiving water. This approach is appropriate for long term human health criteria where critical environmental effects are expected to occur far downstream from the source.”
- For acute and chronic aquatic life criteria: “The discharge to Woods Creek is via a side channel, therefore, complete mixing may not occur.”

The Permit allows for mixing zones for human health based criteria absent any mixing zone analysis. Woods Creek is defined in the Permit, page F-11, as “...a small ephemeral stream ranging in width between 3 ft. to 4 ft...” Therefore per the SIP definition; “complete mixing” must occur within 8 ft of the point of discharge. The Permit was modified by late revision to state that the discharge is completely mixed within 87 to 135 feet downstream of the discharge; clearly not mixed within the terms required by the SIP. Based on the facts presented in the Permit, there is no diffuser and the discharge simply flows into the creek via a side channel, and the statements contained in the Permit; the discharge is not “completely mixed” as defined in the SIP. In accordance with SIP Section 1.4.2, a mixing zone cannot be granted, including for human health criteria, absent a complete and independent mixing zone study. The dilution credits for human health criteria must be removed from the proposed Order and end-of-pipe limitations based solely on the criteria or standards must be developed; specifically for chloroform (cancer potency factor), manganese and nitrate and nitrite.

Woods Creek flows into New Don Pedro Reservoir within a relatively short distance. The Permit was revised by late revision to state that the discharge enters Don Pedro Reservoir approximately two miles downstream of the discharge; and claims absent any documentation that there are no drinking water intakes within this two mile stretch of the creek. There is no information in the record documenting the absence of drinking water intakes; especially potential riparian intakes by adjacent landowners. In any case; such an allowance would at a minimum degrade and eliminate the drinking water beneficial use for two miles of a California waterbody. There is no mixing zone analysis as required for incompletely mixed discharges as required by the SIP and there is no Antidegradation Policy analysis for what is at a minimum removal of the drinking water beneficial use for a two mile stretch of Woods Creek.

The discharge is no completely mixed within the within 8 ft of the point of discharge as is required by the SIP. Confirming this: the Permit was modified to state that the discharge

is mixed within 87 to 135 feet of the point of discharge (without any supporting documentation). In defense of an incompletely mixed discharge/receiving stream:

- The Central Valley Regional Water Quality Control Board’s Basin Plan, page IV-16.00, requires the Regional Board use EPA’s *Technical Support Document for Water Quality Based Toxics Control (TSD)* in assessing mixing zones.
 - Section 4.4.1 General Recommendations for Outfall Design. Of the three types of outfalls, the surface water type is the least favorable for toxic discharges since it offers the least initial mixing. In particular, surface water discharges at the shoreline of a waterbody usually have an impact along the shoreline when there is significant cross flow and thus yield high surface concentrations.
 - Section 4.4.2, 2) Lakes and Reservoirs. All seasonal analyses should assume an ambient velocity of zero unless persistent currents have been documented. Special attention should be given to periods of rising water level since pollutants can move back into coves and accumulate under these conditions.
- The SIP, Section 1.4.2.2 requires that the Regional Board shall consider, if necessary to protect beneficial uses, the level of flushing in water bodies such as lakes and reservoirs where pollutants may not be readily flushed through the system.
 - This Section of the SIP also requires that if a Regional Board allows a mixing zone and dilution credit, the permit shall specify the point in the receiving water where the applicable criteria/objectives must be met. In this case the Permit does not specify where the objective must be met, but states that: “... environmental effects are expected to occur far downstream...”.
- The Basin Plan, Page IV-17.00, allows the Regional Board to grant mixing zones provided that the Discharger has demonstrated that the mixing zone will not adversely impact beneficial uses. The beneficial uses of the receiving stream include municipal and domestic uses. The Permit’s mixing zones allowance does not specify the point of compliance but the mixing zone would apply “far downstream”. The municipal and domestic beneficial uses would be adversely impacted within the mixing zone which extends “far downstream”. The Permit was modified by late revision to state that drinking water beneficial uses to not occur for two miles downstream. The point of compliance was not specified by late revision and monitoring to confirm compliance is not required by the Permit. A complete mixing zone analysis for an incompletely mixed

discharge was not conducted.

- According to faculty at UC Davis; Don Pedro Dam releases water into the Tuolumne River and water is diverted to Modesto and Turlock Irrigation Districts (MID and TID respectively). TID delivers drinking water to about 70 people in La Grange and over 99% of the allocated water is delivered to farmers. MID provides irrigation water to approximately 64,000 acres and a small percent of the water is delivered to supply drinking water in Stanislaus County. Don Pedro reservoir attracts over 400,000 recreational visits per year.

“A mixing zone is an area where an effluent discharge undergoes initial dilution and is extended to cover the secondary mixing in the ambient waterbody. A mixing zone is an allocated impact zone where water quality criteria can be exceeded as long as acutely toxic conditions are prevented” according to EPA’s *Technical Support Document for Water Quality-based Toxics Control* (TSD) (USEPA, 1991), (Water quality criteria must be met at the edge of a mixing zone.) Mixing zones are regions within public waters adjacent to point source discharges where pollutants are diluted and dispersed at concentrations that routinely exceed human health and aquatic life water quality standards (the maximum levels of pollutants that can be tolerated without endangering people, aquatic life, and wildlife.) Mixing zone policies allow a discharger’s point of compliance with state and federal water quality standards to be moved from the “end of the pipe” to the outer boundaries of a dilution zone. The CWA was adopted to minimize and eventually eliminate the release of pollutants into public waters because fish were dying and people were getting sick. The CWA requires water quality standards (WQS) be met in all waters to prohibit concentrations of pollutants at levels assumed to cause harm. Since WQS criteria are routinely exceeded in mixing zones it is likely that in some locations harm is occurring. The general public is rarely aware that local waters are being degraded within these mixing zones, the location of mixing zones within a waterbody, the nature and quantities of pollutants being diluted, the effects the pollutants might be having on human health or aquatic life, or the uses that may be harmed or eliminated by the discharge. Standing waist deep at a favorite fishing hole, a fisherman has no idea that he is in the middle of a mixing zone for pathogens for a sewage discharger that has not been required to adequately treat their waste.

In 1972, backed by overwhelming public support, Congress overrode President Nixon’s veto and passed the Clean Water Act. Under the CWA, states are required to classify surface waters by *uses* – the beneficial purposes provided by the waterbody. For example, a waterbody may be designated as a drinking water source, or for supporting the growth and propagation of aquatic life, or for allowing contact recreation, or as a water source for industrial activities, or all of the above. States must then adopt *criteria* – numeric and narrative limits on pollution, sufficient to protect the uses assigned to the waterbody. *Uses + Criteria = Water Quality Standards (WQS)*. WQS are regulations adopted by each state to protect the waters under their jurisdiction. If a waterbody is classified for more than one use, the applicable WQS are the criteria that would protect the most sensitive use.

All wastewater dischargers to surface waters must apply for and receive a permit to discharge pollutants under the National Pollutant Discharge Elimination System (NPDES.) Every NPDES permit is required to list every pollutant the discharger anticipates will be released, and establish effluent limits for these pollutants to ensure the discharger will achieve WQS. NPDES permits also delineate relevant control measures, waste management procedures, and monitoring and reporting schedules.

It is during the process of assigning effluent limits in NPDES permits that variances such as mixing zones alter the permit limits for pollutants by multiplying the scientifically derived water quality criteria by dilution factors. The question of whether mixing zones are legal has never been argued in federal court.

Mixing zones are never mentioned or sanctioned in the CWA. To the contrary, the CWA appears to speak against such a notion:

“whenever...the discharges of pollutants from a point source...would interfere with the attainment or maintenance of that water quality...which shall assure protection of public health, public water supplies, agricultural and industrial uses, and the protection and propagation of a balanced population of shellfish, fish and wildlife, and allow recreational activities in and on the water, effluent limitations...shall be established which can reasonably be expected to contribute to the attainment or maintenance of such water quality.”

A plain reading of the above paragraph calls for the application of effluent limitations whenever necessary to assure that *WQS will be met in all waters*. Despite the language of the Clean Water Act; US EPA adopted 40 CFR 131.13, General policies, that allows States to, at their discretion, include in their State standards, policies generally affecting their application and implementation, such as mixing zones, low flows and variances. According to EPA; (EPA, Policy and Guidance on Mixing Zones, 63 Fed Reg. 36,788 (July 7, 1998)) as long as mixing zones do not eliminate beneficial uses in the whole waterbody, they do not violate federal regulation or law. California has mixing zone policies included in individual Water Quality Control Plans (Basin Plans) and the *Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California* (2005) permitting pollutants to be diluted before being measured for compliance with the state’s WQS.

Federal Antidegradation regulations at 40 CFR 131.12 require that states protect waters at their present level of quality and that all beneficial uses remain protected. The corresponding State Antidegradation Policy, Resolution 68-16, requires that any degradation of water quality not unreasonably affect present and anticipated beneficial uses. Resolution 68-16 further requires that: “Any activity which produces or may produce or increase volume or concentration of waste and which discharges or proposes to discharge to existing high quality waters will be required to meet waste discharge requirements which will result in the best practicable treatment or control of the discharge necessary to assure that (a) a pollution or nuisance will not occur and (b) the

highest water quality consistent with the maximum benefit to the people of the State will be maintained.”

- Pollution is defined in the California Water Code as an alteration of water quality to a degree which unreasonably affects beneficial uses. In California, Water Quality Control Plans (Basin Plans) contain water quality standards and objectives which are necessary to protect beneficial uses. The Basin Plan for California’s Central Valley Regional Water Board states that: “According to Section 13050 of the California Water Code, Basin Plans consist of a designation or establishment for the waters within a specified area of beneficial uses to be protected, water quality objectives to protect those uses, and a program of implementation needed for achieving the objectives. State law also requires that Basin Plans conform to the policies set forth in the Water Code beginning with Section 13000 and any state policy for water quality control. Since beneficial uses, together with their corresponding water quality objectives, can be defined per federal regulations as water quality standards, the Basin Plans are regulatory references for meeting the state and federal requirements for water quality control (40 CFR 131.20).”
- Nuisance is defined in the California Water Code as anything which is injurious to health, indecent, offensive or an obstruction of the free use of property which affects an entire community and occurs as a result of the treatment or disposal of waste.

The Antidegradation Policy (Resolution 68-16) allows water quality to be lowered as long as beneficial uses are protected (pollution or nuisance will not occur), best practicable treatment and control (BPTC) of the discharge is provided, and the degradation is in the best interest of the people of California. Water quality objectives were developed as the maximum concentration of a pollutant necessary to protect beneficial uses and levels above this concentration would be considered pollution. The Antidegradation Policy does not allow water quality standards and objectives to be exceeded. Mixing zone are regions within public waters adjacent to point source discharges where pollutants are diluted and dispersed at concentrations that routinely exceed water quality standards.

The Antidegradation Policy (Resolution 68-16) requires that best practicable treatment or control (BPTC) of the discharge be provided. Mixing zones have been allowed in lieu of treatment to meet water quality standards at the end-of-the-pipe prior to discharge. To comply with the Antidegradation Policy, the trade of receiving water beneficial uses for lower utility rates must be in the best interest of the people of the state and must also pass the test that the Discharger is providing BPTC. By routinely permitting excessive levels of pollutants to be legally discharged, mixing zones act as an economic disincentive to Dischargers who might otherwise have to design and implement better treatment mechanisms. Although the use of mixing zones may lead to individual, short-term cost savings for the discharger, significant long-term health and economic costs may be

placed on the rest of society. An assessment of BPTC, and therefore compliance with the Antidegradation Policy, must assess whether treatment of the wastestream can be accomplished, is feasible, and not simply the additional costs of compliance with water quality standards. A BPTC case can be made for the benefits of prohibiting mixing zones and requiring technologies that provide superior waste treatment and reuse of the wastestream.

EPA's Water Quality Standards Handbook states that: "It is not always necessary to meet all water quality criteria within the discharge pipe to protect the integrity of the waterbody as a whole." The primary mixing area is commonly referred to as the zone of initial dilution, or ZID. Within the ZID acute aquatic life criteria are exceeded. To satisfy the CWA prohibition against the discharge of toxic pollutants in toxic amounts, regulators assume that if the ZID is small, significant numbers of aquatic organisms will not be present in the ZID long enough to encounter acutely toxic conditions. EPA recommends that a ZID not be located in an area populated by non-motile or sessile organisms, which presumably would be unable to leave the primary mixing area in time to avoid serious contamination.

Determining the impacts and risks to an ecosystem from mixing pollutants with receiving waters at levels that exceed WQS is extremely complex. The range of effects pollutants have on different organisms and the influence those organisms have on each other further compromises the ability of regulators to assess or ensure "acceptable" short and long-term impacts from the use of mixing zones. Few if any mixing zones are examined prior to the onset of discharging for the potential effects on impacted biota (as opposed to the physical and chemical fate of pollutants in the water column). Biological modeling is especially challenging – while severely toxic discharges may produce immediately observable effects, long-term impacts to the ecosystem can be far more difficult to ascertain. The effects of a mixing zone can be insidious; impacts to species diversity and abundance may be impossible to detect until it is too late for reversal or mitigation.

The *CALIFORNIA CONSTITUTION, ARTICLE 10, WATER, SEC. 2* states that: "It is hereby declared that because of the conditions prevailing in this State the general welfare requires that the water resources of the State be put to beneficial use to the fullest extent of which they are capable, and that the waste or unreasonable use or unreasonable method of use of water be prevented, and that the conservation of such waters is to be exercised with a view to the reasonable and beneficial use thereof in the interest of the people and for the public welfare. The right to water or to the use or flow of water in or from any natural stream or water course in this State is and shall be limited to such water as shall be reasonably required for the beneficial use to be served, and such right does not and shall not extend to the waste or unreasonable use or unreasonable method of use or unreasonable method of diversion of water. Riparian rights in a stream or water course attach to, but to no more than so much of the flow thereof as may be required or used consistently with this section, for the purposes for which such lands are, or may be made adaptable, in view of such reasonable and beneficial uses; provided, however, that nothing herein contained shall be construed as depriving any riparian owner of the reasonable use of water of the stream to which the owner's land is riparian under

reasonable methods of diversion and use, or as depriving any appropriator of water to which the appropriator is lawfully entitled. This section shall be self-executing, and the Legislature may also enact laws in the furtherance of the policy in this section contained.” The granting of a mixing zone is an unreasonable use of water when proper treatment of the wastestream can be accomplished to meet end-of-pipe limitations. Also contrary to the California Constitution, a mixing zone does not *serve the beneficial use*; to the contrary, beneficial uses are degraded within the mixing zone.

The Central Valley Regional Water Quality Control Board’s Basin Plan, page IV-16.00, requires the Regional Board use EPA’s *Technical Support Document for Water Quality Based Toxics Control (TSD)* in assessing mixing zones. The TSD, page 70, defines a first stage of mixing, close to the point of discharge, where complete mixing is determined by the momentum and buoyancy of the discharge. The second stage is defined by the TSD where the initial momentum and buoyancy of the discharge are diminished and waste is mixed by ambient turbulence. The TSD goes on to state that in large rivers this second stage mixing may extend for miles. There are drinking water intakes, and proposed intakes, downstream of the wastewater discharge which could be impacted prior to the pollutants from the discharge are completely mixed. The TSD, Section 4.4, requires that if complete mix does not occur in a short distance mixing zone monitoring and modeling must be undertaken.

The State’s *Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays and Estuaries of California (SIP)*, Section 1.4.2.2, contains requirements for a mixing zone study which must be analyzed before a mixing zone is allowed for a wastewater discharge. Properly adopted state Policy requirements are not optional. The proposed Effluent Limitations in the Permit are not supported by the scientific investigation that is required by the SIP and the Basin Plan.

SIP Section 1.4.2.2 requires that a mixing zone shall not:

1. Compromise the integrity of the entire waterbody.
2. Cause acutely toxic conditions to aquatic life.
3. Restrict the passage of aquatic life.
4. Adversely impact biologically sensitive habitats.
5. Produce undesirable aquatic life.
6. Result in floating debris.
7. Produce objectionable color, odor, taste or turbidity.
8. Cause objectionable bottom deposits.
9. Cause Nuisance.
10. Dominate the receiving water body or overlap a different mixing zone.
11. Be allowed at or near any drinking water intake.

The Permit’s mixing zones have not provided a single technical defense to address a single required item of the SIP; the Permit was instead revised by late revision to include unsupported conclusory statements that the terms of the SIP were met.

A very clear unaddressed requirement (SIP Section 1.4.2.2) for mixing zones is that the point(s) in the receiving stream where the applicable criteria must be met shall be specified in the Permit. The “edge of the mixing zone” has not been defined.

Few mixing zones are adequately evaluated to determine whether the modeling exercise was in fact relevant or accurate, or monitored over time to assess the impacts of the mixing zone on the aquatic environment. The sampling of receiving waters often consists of analyzing one or two points where the mixing zone boundary is supposed to be – finding no pollution at the mixing zone boundary is often considered proof that mixing has been “successful” when in fact the sampling protocol might have missed the plume altogether.

The dilution credits for human health criteria must be removed from the proposed Order and end-of-pipe limitations based solely on the criteria or standards must be developed; specifically for chloroform (cancer potency factor), manganese and nitrate and nitrite.

B. The Permit fails to contain an Effluent Limitation for bis(2-ethylhexyl)phthalate despite a clear reasonable potential to exceed waste quality standards in violation of Federal Regulations 40 CFR 122.44.

Bis(2-ethylhexyl)phthalate exceeds water quality standards in the receiving stream at 9.0 $\mu\text{g/l}$, above the CTR Water Quality Standard of 1.8 $\mu\text{g/l}$. Bis(2-ethylhexyl)phthalate has been detected in the wastewater effluent at 11.0 $\mu\text{g/l}$, also above the CTR Water Quality Standard. The Permit Fact Sheet states that the receiving water sampling data for bis(2-ethylhexyl)phthalate is subject to error and is being discarded without any supporting documentation from the laboratory quality assurance/quality control (QA/QC) documents. To the contrary, bis(2-ethylhexyl)phthalate is used in the formation of plastics and has been documented in the available literature to be present in plastic pipes, bottles, bags and widely distributed throughout the environment. The Regional Board total disregards scientific methods, specifically sampling and laboratory QA/QC methodologies, in throwing out data points that would lead to a reasonable potential for a pollutant to exceed water quality standards when the burden should properly be placed on wastewater Dischargers to conduct proper sampling and analysis. The California Water Code (CWC), Section 13377 states in part that: “...the state board or the regional boards shall...issue waste discharge requirements...which apply and ensure compliance with ...water quality control plans, or for the protection of beneficial uses...” Section 122.44(d) of 40 CFR requires that permits include water quality-based effluent limitations (WQBELs) to attain and maintain applicable numeric and narrative water quality criteria to protect the beneficial uses of the receiving water. Failure to include an effluent limitation for bis(2-ethylhexyl)phthalate in the Permit violates 40 CFR 122.44 and CWC 13377.

C. The Permit fails to contain mass-based effluent limits for chlorine, manganese, nitrate and nitrite, oil and grease, copper and zinc as required by Federal Regulations 40 CFR 122.45(b).

Federal Regulation, 40 CFR 122.45 (b) requires that in the case of POTWs, permit Effluent Limitations, standards, or prohibitions shall be based on design flow. Concentration is not a basis for design flow. Mass limitations are concentration multiplied by the design flow and therefore meet the regulatory requirement.

Section 5.7.1 of U.S. EPA's *Technical Support Document for Water Quality Based Toxics Control* (TSD, EPA/505/2-90-001) states with regard to mass-based Effluent Limits:

“Mass-based effluent limits are required by NPDES regulations at 40 CFR 122.45(f). The regulation requires that all pollutants limited in NPDES permits have limits, standards, or prohibitions expressed in terms of mass with three exceptions, including one for pollutants that cannot be expressed appropriately by mass. Examples of such pollutants are pH, temperature, radiation, and whole effluent toxicity. Mass limitations in terms of pounds per day or kilograms per day can be calculated for all chemical-specific toxics such as chlorine or chromium. Mass-based limits should be calculated using concentration limits at critical flows. For example, a permit limit of 10 mg/l of cadmium discharged at an average rate of 1 million gallons per day also would contain a limit of 38 kilograms/day of cadmium.

Mass based limits are particularly important for control of bioconcentratable pollutants. Concentration based limits will not adequately control discharges of these pollutants if the effluent concentrations are below detection levels. For these pollutants, controlling mass loadings to the receiving water is critical for preventing adverse environmental impacts.

However, mass-based effluent limits alone may not assure attainment of water quality standards in waters with low dilution. In these waters, the quantity of effluent discharged has a strong effect on the instream dilution and therefore upon the RWC. At the extreme case of a stream that is 100 percent effluent, it is the effluent concentration rather than the mass discharge that dictates the instream concentration. Therefore, EPA recommends that permit limits on both mass and concentration be specified for effluents discharging into waters with less than 100 fold dilution to ensure attainment of water quality standards.”

Federal Regulations, 40 CFR 122.45 (f), states the following with regard to mass limitations:

- “(1) all pollutants limited in permits shall have limitations, standards, or prohibitions expressed in terms of mass except:
 - (i) For pH, temperature, radiation or other pollutants which cannot be expressed by mass;
 - (ii) When applicable standards and limitations are expressed in terms of other units of measurement; or
 - (iii) If in establishing permit limitations on a case-by-case basis under 125.3, limitations expressed in terms of mass are infeasible because the mass of

the pollutant discharged cannot be related to a measure of operation (for example, discharges of TSS from certain mining operations), and permit conditions ensure that dilution will not be used as a substitute for treatment.

(2) Pollutants limited in terms of mass additionally may be limited in terms of other units of measurement, and the permit shall require the permittee to comply with both limitations.”

There is no explanation in the Permit why mass limitations are infeasible.

Federal Regulations, 40 CFR 122.45 (B)(1), states the following: “In the case of POTWs, permit effluent limitations, standards, or prohibitions shall be calculated based on design flow.”

Traditional wastewater treatment plant design utilizes average dry weather flow rates for organic, individual constituent, loading rates and peak wet weather flow rates for hydraulic design of pipes, weir overflow rates, and pumps.

Increased wet weather flow rates are typically caused by inflow and infiltration (I/I) into the sewer collection system that dilutes constituent loading rates and does not add to the mass of wastewater constituents.

For POTWs priority pollutants, such as metals, have traditionally been reduced by the reduction of solids from the wastestream, incidental to treatment for organic material. Following adoption of the CTR, compliance with priority pollutants is of critical importance and systems will need to begin utilizing loading rates of individual constituents in the WWTP design process. It is highly likely that the principal design parameters for individual priority pollutant removal will be based on mass, making mass based Effluent Limitations critically important to compliance. The inclusion of mass limitations will be of increasing importance to achieving compliance with requirements for individual pollutants.

As systems begin to design to comply with priority pollutants, the design systems for POTWs will be more sensitive to similar restrictions as industrial dischargers currently face where production rates (mass loadings) are critical components of treatment system design and compliance. Currently, Industrial Pretreatment Program local limits are frequently based on mass. Failure to include mass limitations would allow industries to discharge mass loads of individual pollutants during periods of wet weather when a dilute concentration was otherwise observed, upsetting treatment processes, causing effluent limitation processes, sludge disposal issues, or problems in the collection system.

In addition to the above citations, on June 26th 2006 U.S. EPA, Mr. Douglas Eberhardt, Chief of the CWA Standards and Permits Office, sent a letter to Dave Carlson at the Central Valley Regional Water Quality Control Board strongly recommending that

NPDES permit effluent limitations be expressed in terms of mass as well as concentration.

D. The few mass limitations for BOD, TSS and ammonia, and the discharge flow limitation in the Permit are not based on design flow as is required by Federal Regulation 40 CFR 122.45 (B)(1).

Federal Regulations, 40 CFR 122.45 (B)(1), states the following: “In the case of POTWs, permit effluent limitations, standards, or prohibitions shall be calculated based on design flow.” Footnote No. 1 to Table 6 Effluent Limitations and Effluent Limitation No. e state that the mass limitations are based on a monthly average discharge flow of 2.9 mgd as limited by Effluent Limitation No. e. As is explained in the Permit Fact Sheet, Flow, page F-10, the flow rate of 2.9 mgd is the level of flow necessary to accommodate discharges from the effluent storage reservoir. The storage capabilities of the reservoir have no relationship to the mass of pollutants that can be treated at the wastewater treatment plant. The design flow of the wastewater treatment plant is 2.6 mgd (average dry weather flow (Fact Sheet F-10)). The Permit Effluent Limitations for mass and the discharge flow limitation is not based on the design capability of the wastewater treatment plant and violates the requirement of 40 CFR 122.45 (B)(1).

E. The Permit contains an Effluent Limitation for acute toxicity that allows mortality to aquatic life that exceeds the Basin Plan water quality objective and does not comply with Federal regulations, at 40 CFR 122.44 (d)(1)(i) or the Clean Water Act.

Under the federal Clean Water Act (CWA), states are required to classify surface waters by *uses* – the beneficial purposes provided by the waterbody. For example, a waterbody may be designated as a drinking water source, or for supporting the growth and propagation of aquatic life, or for allowing contact recreation, or as a water source for industrial activities, or all of the above. States must then adopt *criteria* – numeric and narrative limits on pollution, sufficient to protect the uses assigned to the waterbody. Federal regulations, at 40 CFR 122.44 (d)(1)(i), adopted to require implementation of the CWA, require that limitations must control all pollutants or pollutant parameters which the Director determines are or may be discharged at a level which will cause, or contribute to an excursion above any State water quality standard, including State narrative criteria for water quality. The Water Quality Control Plan for the Sacramento/San Joaquin River Basins (Basin Plan), Water Quality Objectives (Page III-8.00), for Toxicity is a narrative criteria which states that all waters shall be maintained free of toxic substances in concentrations that produce detrimental physiological responses in human, plant, animal, or aquatic life. This section of the Basin Plan further states, in part that, compliance with this objective will be determined by analysis of indicator organisms (toxicity tests).

The Permit requires that the Discharger conduct acute toxicity tests and states that compliance with the toxicity objective will be determined by analysis of indicator organisms. However, the Tentative Permit contains a discharge limitation that allows

30% mortality (70% survival) of fish species in any given toxicity test. Surely, mortality is a detrimental physiological response to aquatic life.

For an ephemeral or low flow stream, allowing 30% mortality in acute toxicity tests allows that same level of mortality in the receiving stream, in violation of federal regulations and contributes to exceedance of the Basin Plan's narrative water quality objective for toxicity. In receiving streams where dilution may be available the primary mixing area is commonly referred to as the zone of initial dilution, or ZID. Within the ZID acute aquatic life criteria are exceeded. To satisfy the CWA prohibition against the discharge of toxic pollutants in toxic amounts, regulators assume that if the ZID is small, significant numbers of aquatic organisms will not be present in the ZID long enough to encounter acutely toxic conditions. The allowance of 30% mortality will result in acute toxicity within the ZID. Before the discharge can be allowed a complete mixing zone analysis is required in accordance with the Basin Plan and the *Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California* (SIP) to show that discharge limitations prevent toxicity; such an analysis has not been completed. CWC Sections 13146 and 13247 require that the Board in carrying out activities which affect water quality shall comply with state policy for water quality control unless otherwise directed by statute, in which case they shall indicate to the State Board in writing their authority for not complying with such policy. The State Board has adopted the SIP and the Regional Board is required to the Policy.

US EPA's *Technical Support Document for Water Quality-based Toxics Control* states, on page 104, that:

“When setting a whole effluent toxicity limit to protect against acute effects, some permitting authorities use an end-of-pipe approach. Typically these limits are established as an LC50>100% effluent at the end of the pipe. These limits are routinely set without any consideration as to the fate of the effluent and the concentrations of toxicant(s) after the discharge enters the receiving water. Limits derived in this way are not water quality based limits and suffer from significant deficiencies since the toxicity of a pollutant depends mostly upon concentration, duration of exposure, and repetitiveness of the exposure. This is especially true in effluent dominated waters. For example, an effluent that has an LC50=100% contains enough toxicity to be lethal up to 50% of the test organisms. If the effluent is discharged to a low flow receiving waterbody that provides no more than a three fold dilution at the critical flow, significant mortality can occur in the receiving water. Furthermore, such a limit could not assure protection against chronic effects in the receiving waterbody. Chronic effects could occur if the dilution in the receiving water multiplied by the acute to chronic ratio is greater than 100 percent. Therefore, in effluent dominated situations, limits set using this approach may be severely underprotective. In contrast, whole effluent toxicity limits set using this approach in very high receiving water flow conditions may be overly restrictive.”

Following US EPA's rationale the limitations of allowing 70% survival (30% mortality) in acute toxicity tests, as is the case in the cited LC50, will result in the allowance of toxic discharges to ephemeral streams, which is representative of the receiving waters at Davis. While the State and Regional Board's method of prescribing an effluent limitation of 70% percent survival may be protective in waterbodies with significant dilution; such a limitation should be subject to a complete mixing zone analysis. For an ephemeral receiving stream a mixing zone analysis would not be applicable under worst case dry stream conditions. The Order should be revised to require the Regional Board to prohibit acute toxicity (100% survival as compared to the laboratory control) in accordance with Federal regulations, at 40 CFR 122.44 (d)(1)(i).

With regard to WET testing variability; US EPA's *Technical Support Document for Water Quality-based Toxics Control* states, on page 11, that:

“In summary, whole effluent toxicity testing can represent practical tests that estimate potential receiving water impacts. Permit limits that are developed correctly from whole effluent toxicity tests should protect biota if the discharged effluent meets the limits. It is important not confuse permit limit variability with toxicity test variability” (emphasis added)

Response to Comments presented by the Regional Board state in part that: “The acute whole effluent toxicity limits establish thresholds to control acute toxicity in the effluent: survival in one test no less than 70% and a median of no less than 90% survival in three consecutive tests. Some in-test mortality can occur by chance. To account for this, the acute toxicity test acceptability criteria allow ten percent mortality (requires 90% survival) in the control. Thus, the acute toxicity limits allow for some test variability, but impose ceilings for exceptional events (i.e., 30% mortality or more), and for repeat events (i.e., median of three events exceeding mortality of 10%). These effluent limitations are consistent with U.S. EPA guidance.” The comment fails to recognize that test variability is accounted for in the laboratory control. If the laboratory control fails to provide 100% survival of the test species, the test results are modified accordingly. The Regional Board has confused permit limit variability with toxicity test variability as was predicted by the SIP.

The Permit must be revised to prohibit acute toxicity, require 100% survival in toxicity tests, in accordance with Federal regulations, at 40 CFR 122.44 (d)(1)(i), the CWA, the SIP, the CWC and the Basin Plan.

F. The Permit does not contain Effluent Limitations for chronic toxicity and therefore does not comply with Federal regulations, at 40 CFR 122.44 (d)(1)(i) and the *Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California* (SIP).

Permit, State Implementation Policy states that: “On March 2, 2000, the State Water Board adopted the *Policy for Implementation of Toxics Standards for Inland Surface Waters, Enclosed Bays, and Estuaries of California* (State Implementation Policy or SIP).

The SIP became effective on April 28, 2000 with respect to the priority pollutant criteria promulgated for California by the USEPA through the NTR and to the priority pollutant objectives established by the Regional Water Board in the Basin Plan. The SIP became effective on May 18, 2000 with respect to the priority pollutant criteria promulgated by the USEPA through the CTR. The State Water Board adopted amendments to the SIP on February 24, 2005 that became effective on July 13, 2005. The SIP establishes implementation provisions for priority pollutant criteria and objectives and provisions for chronic toxicity control. Requirements of this Order implement the SIP.”

The SIP, Section 4, Toxicity Control Provisions, Water Quality-Based Toxicity Control, states that: “A chronic toxicity effluent limitation is required in permits for all dischargers that will cause, have a reasonable potential to cause, or contribute to chronic toxicity in receiving waters.” The SIP is a state *Policy* and CWC Sections 13146 and 13247 require that the Board in carrying out activities which affect water quality shall comply with state policy for water quality control unless otherwise directed by statute, in which case they shall indicate to the State Board in writing their authority for not complying with such policy.

Federal regulations, at 40 CFR 122.44 (d)(1)(i), require that limitations must control all pollutants or pollutant parameters which the Director determines are or may be discharged at a level which will cause, or contribute to an excursion above any State water quality standard, including state narrative criteria for water quality. There has been no argument that domestic sewage contains toxic substances and presents a reasonable potential to cause toxicity if not properly treated and discharged. The Water Quality Control Plan for the Sacramento/ San Joaquin River Basins (Basin Plan), Water Quality Objectives (Page III-8.00) for Toxicity is a narrative criteria which states that all waters shall be maintained free of toxic substances in concentrations that produce detrimental physiological responses in human, plant, animal, or aquatic life. The Permit states that: “...to ensure compliance with the Basin Plan’s narrative toxicity objective, the discharger is required to conduct whole effluent toxicity testing...”. However, sampling does not equate with or ensure compliance. The Tentative Permit requires the Discharger to conduct an investigation of the possible sources of toxicity if a threshold is exceeded. This language is not a limitation and essentially eviscerates the Regional Board’s authority, and the authority granted to third parties under the Clean Water Act, to find the Discharger in violation for discharging chronically toxic constituents. An effluent limitation for chronic toxicity must be included in the Order. In addition, the Chronic Toxicity Testing Dilution Series should bracket the actual dilution at the time of discharge, not use default values that are not relevant to the discharge.

Permit is quite simply wrong; by failing to include effluent limitations prohibiting chronic toxicity the Permit does not “...implement the SIP”. The Regional Board has commented time and again that no chronic toxicity effluent limitations are being included in NPDES permit until the State Board adopts a numeric limitation. The Regional Board explanation does not excuse the Permit’s failure to comply with Federal Regulations, the SIP, the Basin Plan and the CWC. The Regional Board’s Basin Plan, as cited above, already states that: “...waters shall be maintained free of toxic substances in

concentrations that produce detrimental physiological responses...” Accordingly, the Permit must be revised to prohibit chronic toxicity (mortality and adverse sublethal impacts to aquatic life, (sublethal toxic impacts are clearly defined in EPA’s toxicity guidance manuals)) in accordance with Federal regulations, at 40 CFR 122.44 (d)(1)(i) and the Basin Plan and the SIP.

G. The Permit contains a requirement, Best Management Practices and Pollution Prevention, that the Discharger continue to spray or flood irrigate fodder crops and pasture lands with reclaimed water yet fails to contain limitations that are protective of the underlying groundwater or require compliance with applicable law (CCR Title 27).

Existing WDRs, Order No. R5-2002-0202, for land disposal show that the soil mantle in the area is thin, approximately less than 5 inches and that the thin soil mantle overlies fractured bedrock. Quartz Reservoir utilized for the storage of treated wastewater is only partially lined and has been shown to percolate up to 258,600 gallons per day. The underlying groundwater is utilized for domestic and irrigation uses pumped from wells within the fractured bedrock.

The Permit requires that secondary wastewater discharges to surface waters can only occur when there is a minimum of a twenty to one dilution ratio available in the receiving waters to protect the public’s health and the irrigated agriculture and contact recreational uses of the receiving stream. The Permit does not discuss the fact that an even higher level of treatment is necessary to protect domestic and municipal beneficial uses.

The Permit requires that wastewater with this same level of treatment be discharged to areas with high percolation rates and underlying fractured bedrock; the groundwater from these fractures is known to be the source water for drinking water and irrigation. There is no documented dilution available within the groundwater aquifer. The same level of protection provided surface waters is not being provided for groundwater quality and the beneficial uses of groundwater and that level of treatment would not be protective of the drinking water beneficial use of surface water or groundwater for pathogens.

CCR Title 27, §20090. SWRCB - Exemptions. (C15: §2511): The following activities shall be exempt from the SWRCB-promulgated provisions of this subdivision, so long as the activity meets, and continues to meet, all preconditions listed: (a) **Sewage—** Discharges of domestic sewage or treated effluent which are regulated by WDRs issued pursuant to Chapter 9, Division 3, Title 23 of this code, or for which WDRs have been waived, and which are consistent with applicable water quality objectives, and treatment or storage facilities associated with municipal wastewater treatment plants, provided that residual sludges or solid waste from wastewater treatment facilities shall be discharged only in accordance with the applicable SWRCB-promulgated provisions of this division.

Region 5’s Basin Plan, *Water Quality Objectives For Ground Waters*, The following objectives apply to all ground waters of the Sacramento and San Joaquin River Basins, as the objectives are relevant to the protection of designated beneficial uses. These

objectives do not require improvement over naturally occurring background concentrations. The ground water objectives contained in this plan are not required by the federal Clean Water Act.

Bacteria

In ground waters used for domestic or municipal supply (MUN) the most probable number of coliform organisms over any seven-day period shall be less than 2.2/100 ml.

Chemical Constituents

Ground waters shall not contain chemical constituents in concentrations that adversely affect beneficial uses. At a minimum, ground waters designated for use as domestic or municipal supply (MUN) shall not contain concentrations of chemical constituents in excess of the maximum contaminant levels (MCLs) specified in the following provisions of Title 22 of the California Code of Regulations, which are incorporated by reference into this plan: Tables 64431-A (Inorganic Chemicals) and 64431-B (Fluoride) of Section 64431, Table 64444-A (Organic Chemicals) of Section 64444, and Tables 64449-A (Secondary Maximum Contaminant Levels- Consumer Acceptance Limits) and 64449-B (Secondary Maximum Contaminant Levels-Ranges) of Section 64449. This incorporation-by-reference is prospective, including future changes to the incorporated provisions as the changes take effect. At a minimum, water designated for use as domestic or municipal supply (MUN) shall not contain lead in excess of 0.015 mg/l. To protect all beneficial uses, the Regional Water Board may apply limits more stringent than MCLs.

Tastes and Odors

Ground waters shall not contain taste- or odor producing substances in concentrations that cause nuisance or adversely affect beneficial uses.

Toxicity

Ground waters shall be maintained free of toxic substances in concentrations that produce detrimental physiological responses in human, plant, animal, or aquatic life associated with designated beneficial use(s). This objective applies regardless of whether the toxicity is caused by a single substance or the interactive effect of multiple substances.

The exemption from CCR Title 27 requirements contains the precondition that the discharge does not degrade groundwater to levels that exceed water quality objectives of the Basin Plan. This precondition has not been met. The threat to the underlying groundwater quality is not assessed in the Permit although land disposal with resulting percolation is required. The failure to protect groundwater quality while requiring a wastewater discharge to groundwater violates California Water Code, section 13377, which requires that: "Notwithstanding any other provision of this division, the state board and the regional boards shall, as required or authorized by the Federal Water Pollution Control Act, as amended, issue waste discharge and dredged or fill material permits which apply and ensure compliance with all applicable provisions of the act and acts amendatory thereof or supplementary, thereto, together with any more stringent effluent

standards or limitations necessary to implement water quality control plans, or for the protection of beneficial uses, or to prevent nuisance.”

H. The Permit establishes Effluent Limitations for metals based on the hardness of the effluent as opposed to the ambient upstream receiving water hardness as required by Federal Regulations, the California Toxics Rule (CTR, 40 CFR 131.38(c)(4)).

Federal Regulation 40 CFR 131.38(c)(4) states that: “For purposes of calculating freshwater aquatic life criteria for metals from the equations in paragraph (b)(2) of this section, for waters with a hardness of 400 mg/l or less as calcium carbonate, the actual ambient hardness of the surface water shall be used in those equations.” (Emphasis added). Attachment G, of the Permit, is a summary of the reasonable potential analysis. Footnotes No. 8, 9 and 10, of Attachment G, state that the effluent hardness was used to calculate Effluent Limitations for metals (copper, cadmium, silver and zinc).

The Permit Fact Sheet goes into great detail citing the Federal Regulation requiring the receiving water hardness be used to establish Effluent Limitations. The Permit states that the effluent hardness and the downstream hardness were used to calculate Effluent Limitations for metals. The definition of *ambient* is “in the surrounding area”, “encompassing on all sides”. It has been the Region 5, Sacramento, NPDES Section, in referring to Basin Plan objectives for temperature, to define *ambient* as meaning upstream. It is reasonable to assume, after considering the definition of ambient, that EPA is referring to the hardness of the receiving stream before it is potentially impacted by an effluent discharge. It is also reasonable to make this assumption based on past interpretations and since EPA, in permit writers’ guidance and other reference documents, generally assumes receiving streams have dilution, which would ultimately “encompass” the discharge. Ambient conditions are in-stream conditions unimpacted by the discharge.

The Federal Register, Volume 65, No. 97/Thursday, May 18th 2000 (31692), adopting the California Toxics Rule in confirming that the ambient hardness is the upstream hardness, absent the wastewater discharge, states that: “A hardness equation is most accurate when the relationship between hardness and the other important inorganic constituents, notably alkalinity and pH, are nearly identical in all of the dilution waters used in the toxicity tests and in the surface waters to which the equation is to be applied. If an effluent raises hardness but not alkalinity and/or pH, using the lower hardness of the downstream hardness might provide a lower level of protection than intended by the 1985 guidelines. If it appears that an effluent causes hardness to be inconsistent with alkalinity and/or pH the intended level of protection will usually be maintained or exceeded if either (1) data are available to demonstrate that alkalinity and/or pH do not affect the toxicity of the metal, or (2) the hardness used in the hardness equation is the hardness of upstream water that does not include the effluent. The level of protection intended by the 1985 guidelines can also be provided by using the WER procedure.”

Once again the public is subject to a bureaucrat “knowing better” and simply choosing to ignore very clear regulatory requirements. The Regional Board staff have chosen to deliberately ignore Federal Regulations placing themselves above the law. There are procedures for changing regulations if peer reviewed science indicates the need to do so, none of which have been followed. The Permit failure to include Effluent Limitations for copper, cadmium, silver and zinc based on the actual ambient hardness of the surface water is contrary to the cited Federal Regulation and must be amended to comply with the cited regulatory requirement.

I. The Permit contains an inadequate reasonable potential which resulted in Effluent Limitations for Aluminum, Foaming Agents (MBAS) and chloride being excluded from the Order by using incorrect statistical multipliers.

Federal regulations, 40 CFR § 122.44(d)(1)(ii), state “when determining whether a discharge causes, has the reasonable potential to cause, or contributes to an in-stream excursion above a narrative or numeric criteria within a State water quality standard, the permitting authority shall use procedures which account for existing controls on point and nonpoint sources of pollution, **the variability of the pollutant or pollutant parameter in the effluent**, the sensitivity of the species to toxicity testing (when evaluating whole effluent toxicity), and where appropriate, the dilution of the effluent in the receiving water.” Emphasis added.

Table F-5: The reasonable potential analyses for CTR constituents fail to consider the statistical variability of data and laboratory analyses as explicitly required by the federal regulations. The procedures for computing variability are detailed in Chapter 3, pages 52-55, of US EPA’s *Technical Support Document for Water Quality-based Toxics Control* and would have resulted in the addition of Effluent Limitations for aluminum, MBAS and chloride. Federal Regulations, 40 CFR 122.44 (d)(i), requires that; “Limitations must control all pollutants or pollutant parameters (either conventional, nonconventional, or toxic pollutants) which the Director determines are or may be discharged at a level which will cause, have the reasonable potential to cause, or contribute to an excursion above any State water quality standard, including State narrative criteria for water quality.” The reasonable potential analyses for CTR constituents are flawed and must be recalculated. The fact that the SIP illegally ignores this fundamental requirement does not exempt the Regional Board from its obligation to consider statistical variability in compliance with federal regulations.

J. The Permit contains Effluent Limitations less stringent than the existing permit for settleable solids and chlorine contrary to the Antibacksliding requirements of the Clean Water Act and Federal Regulations, 40 CFR 122.44 (l)(1).

Under the Clean Water Act (CWA), point source dischargers are required to obtain federal discharge (NPDES) permits and to comply with water quality based effluent limits (WQBELs) in NPDES permits sufficient to make progress toward the achievement of water quality standards or goals. The antibacksliding and antidegradation rules clearly

spell out the interest of Congress in achieving the CWA's goal of continued progress toward eliminating all pollutant discharges. Congress clearly chose an overriding environmental interest in clean water through discharge reduction, imposition of technological controls, and adoption of a rule against relaxation of limitations once they are established.

Upon permit reissuance, modification, or renewal, a discharger may seek a relaxation of permit limitations. However, according to the CWA, relaxation of a WQBEL is permissible only if the requirements of the antibacksliding rule are met. The antibacksliding regulations prohibit EPA from reissuing NPDES permits containing interim effluent limitations, standards or conditions less stringent than the final limits contained in the previous permit, with limited exceptions. These regulations also prohibit, with some exceptions, the reissuance of permits originally based on best professional judgment (BPJ) to incorporate the effluent guidelines promulgated under CWA §304(b), which would result in limits less stringent than those in the previous BPJ-based permit. Congress statutorily ratified the general prohibition against backsliding by enacting §§402(o) and 303(d)(4) under the 1987 Amendments to the CWA. The amendments preserve present pollution control levels achieved by dischargers by prohibiting the adoption of less stringent effluent limitations than those already contained in their discharge permits, except in certain narrowly defined circumstances.

When attempting to backslide from WQBELs under either the antidegradation rule or an exception to the antibacksliding rule, relaxed permit limits must not result in a violation of applicable water quality standards. The general prohibition against backsliding found in §402(o)(1) of the Act contains several exceptions. Specifically, under §402(o)(2), a permit may be renewed, reissued, or modified to contain a less stringent effluent limitation applicable to a pollutant *if*: (A) material and substantial alterations or additions to the permitted facility occurred after permit issuance which justify the application of a less stringent effluent limitation; (B)(i) information is available which was not available at the time of permit issuance (other than revised regulations, guidance, or test methods) and which would have justified the application of a less stringent effluent limitation at the time of permit issuance; or (ii) the Administrator determines that technical mistakes or mistaken interpretations of law were made in issuing the permit under subsection (a)(1)(B) of this section; (C) a less stringent effluent limitation is necessary because of events over which the permittee has no control and for which there is no reasonably available remedy [(e.g., Acts of God)]; (D) the permittee has received a permit modification under section 1311(c), 1311(g), 1311(h), 1311(i), 1311(k), 1311(n), or 1326(a) of this title; or (E) the permittee has installed the treatment facilities required to meet the effluent limitations in the previous permit, and has properly operated and maintained the facilities, but has nevertheless been unable to achieve the previous effluent limitations, in which case the limitations in the reviewed, reissued, or modified permit may reflect the level of pollutant control actually achieved (but shall not be less stringent than required by effluent guidelines in effect at the time of permit renewal, reissuance, or modification).

Even if a discharger can meet either the requirements of the antidegradation rule under §303(d)(4) or one of the statutory exceptions listed in §402(o)(2), there are still limitations as to how far a permit may be allowed to backslide. Section 402(o)(3) acts as a floor to restrict the extent to which BPJ and water quality-based permit limitations may be relaxed under the antibacksliding rule. Under this subsection, even if EPA allows a permit to backslide from its previous permit requirements, EPA may never allow the reissued permit to contain effluent limitations which are less stringent than the current effluent limitation guidelines for that pollutant, or which would cause the receiving waters to violate the applicable state water quality standard adopted under the authority of §303.49.

Federal regulations 40 CFR 122.44 (l)(1) have been adopted to implement the antibacksliding requirements of the CWA:

(l) Reissued permits. (1) Except as provided in paragraph (l)(2) of this section when a permit is renewed or reissued, interim effluent limitations, standards or conditions must be at least as stringent as the final effluent limitations, standards, or conditions in the previous permit (unless the circumstances on which the previous permit was based have materially and substantially changed since the time the permit was issued and would constitute cause for permit modification or revocation and reissuance under Sec. 122.62.)

(2) In the case of effluent limitations established on the basis of Section 402(a)(1)(B) of the CWA, a permit may not be renewed, reissued, or modified on the basis of effluent guidelines promulgated under section 304(b) subsequent to the original issuance of such permit, to contain effluent limitations which are less stringent than the comparable effluent limitations in the previous permit.

(i) Exceptions--A permit with respect to which paragraph (l)(2) of this section applies may be renewed, reissued, or modified to contain a less stringent effluent limitation applicable to a pollutant, if:

(A) Material and substantial alterations or additions to the permitted facility occurred after permit issuance which justify the application of a less stringent effluent limitation;

(B)(1) Information is available which was not available at the time of permit issuance (other than revised regulations, guidance, or test methods) and which would have justified the application of a less stringent effluent limitation at the time of permit issuance; or (2) The Administrator determines that technical mistakes or mistaken interpretations of law were made in issuing the permit under section 402(a)(1)(b);

(C) A less stringent effluent limitation is necessary because of events over which the permittee has no control and for which there is no reasonably available remedy;

(D) The permittee has received a permit modification under section 301(c), 301(g), 301(h), 301(i), 301(k), 301(n), or 316(a); or

(E) The permittee has installed the treatment facilities required to meet the effluent limitations in the previous permit and has properly operated and maintained the facilities but has nevertheless been unable to achieve the previous effluent limitations, in which case the limitations in the reviewed, reissued, or modified permit may reflect the level of pollutant control actually achieved (but shall not be less stringent than required by effluent guidelines in effect at the time of permit renewal, reissuance, or modification).

(ii) Limitations. In no event may a permit with respect to which paragraph (1)(2) of this section applies be renewed, reissued, or modified to contain an effluent limitation which is less stringent than required by effluent guidelines in effect at the time the permit is renewed, reissued, or modified. In no event may such a permit to discharge into waters be renewed, issued, or modified to contain a less stringent effluent limitation if the implementation of such limitation would result in a violation of a water quality standard under section 303 applicable to such waters.

The chlorine limitations from the existing Permit are 1-hour and 4-day averages of 0.011 mg/l and 0.019 mg/l, respectively. The Permit relaxes those limitations to 0.01 mg/l and 0.02 mg/l as average monthly and maximum daily (24 hour average) limitations, respectively. The Discharger uses chlorine to disinfect the wastewater. Chlorine is toxic to aquatic life. The simple fact that chlorine is used to disinfect the wastewater is sufficient to present a reasonable potential to exceed water quality objectives (Toxicity). Continuous chlorine monitoring is conducted at most wastewater treatment plants that discharge to surface waters in the Central Valley and is considered best practicable treatment and control (BPTC) of the discharge as is required by the Board's Antidegradation Policy (Resolution 68-16). Continuous monitoring equipment is typically setup to trip an alarm in case of a violation which can reduce or eliminate toxic discharges to surface waters. The rationale presented for the reduction is to avoid requiring the Discharger to provide continuous monitoring for chlorine which the Permit states is necessary for assuring compliance with a one-hour average limitation. The Permit does not appear to recognize that a Maximum Daily Effluent Limitation (MDEL) is defined as a 24 – hour average. In any case, the Permit does not cite a single exception as allowed under the Federal Regulations to justify backsliding and modification of the chlorine effluent limitation.

Settle solids (SS) limitations are technology based on the capability of domestic wastewater treatment systems essentially to assure that solids are not being discharged from the unit processes. The limitations also protect the beneficial uses of receiving waters and the Basin Plan water quality objective for settleable matter. Again, the Permit does not cite a single exception as allowed under the Federal Regulations to justify backsliding and modification of the settleable solids effluent limitation.

K. The Permit contains an inadequate antidegradation analysis that does not comply with the requirements of Section 101(a) of the Clean Water Act, Federal Regulations 40 CFR § 131.12, the State Board's Antidegradation

Policy (Resolution 68-16) and California Water Code (CWC) Sections 13146 and 13247.

There is nothing resembling an analysis buttressing the unsupported claim that BPTC is being provided. To the contrary, if the wastewater treatment system is currently providing BPTC, why the Permit contain compliance schedules for copper, zinc and ammonia? The facility is not in compliance and meeting water quality objectives. The Antidegradation Policy discussion does not discuss underlying groundwater quality even though the Permit requires that wastewater be reclaimed in areas where there is hardly any soil structure and underlying fractures in bedrock may be carrying secondary quality wastes directly to drinking water wells. The Permit does not discuss the drinking water beneficial uses of receiving waters and the proposal to allow a mixing zone that would extend for miles downstream; degrading that use. There is nothing in the Permit resembling an analysis that ensures that existing beneficial uses are protected. In fact, there is almost no information or discussion on the composition and health of the identified beneficial uses. Any reasonably adequate antidegradation analysis must discuss the affected beneficial uses (i.e., numbers and health of the aquatic ecosystem; extent, composition and viability of agricultural production; people depending upon these waters for water supply; extent of recreational activity; etc.) and the probable effect the discharge will have on these uses. The Permit was revised by late revision to state that the discharge enters Don Pedro Reservoir approximately two miles downstream of the discharge; and claims absent any documentation that there are no drinking water intakes within this two mile stretch of the creek. There is no information in the record documenting the absence of drinking water intakes; especially potential riparian intakes by adjacent landowners. In any case; such an allowance would at a minimum degrade and eliminate the drinking water beneficial use for two miles of a California waterbody. There is no mixing zone analysis as required for incompletely mixed discharges as required by the SIP and there is no Antidegradation Policy analysis for what is at a minimum removal of the drinking water beneficial use for a two mile stretch of Woods Creek. The antidegradation analysis in the Permit is not simply deficient, it is literally nonexistent. The brief discussion of antidegradation requirements, in the Findings and Fact Sheet, consist only of skeletal, unsupported, undocumented conclusory statements totally lacking in factual analysis. NPDES permits must include any more stringent effluent limitation necessary to implement the Regional Board Basin Plan (Water Code 13377). The Permit fails to properly implement the Basin Plan's Antidegradation Policy.

CWC Sections 13146 and 13247 require that the Board in carrying out activities which affect water quality shall comply with state policy for water quality control unless otherwise directed by statute, in which case they shall indicate to the State Board in writing their authority for not complying with such policy. The State Board has adopted the Antidegradation Policy (Resolution 68-16), which the Regional Board has incorporated into its Basin Plan. The Regional Board is required by the CWC to comply with the Antidegradation Policy.

Section 101(a) of the Clean Water Act (CWA), the basis for the antidegradation policy, states that the objective of the Act is to "restore and maintain the chemical, biological and

physical integrity of the nation's waters." Section 303(d)(4) of the CWA carries this further, referring explicitly to the need for states to satisfy the antidegradation regulations at 40 CFR § 131.12 before taking action to lower water quality. These regulations (40 CFR § 131.12(a)) describe the federal antidegradation policy and dictate that states must adopt both a policy at least as stringent as the federal policy as well as implementing procedures.

California's antidegradation policy is composed of both the federal antidegradation policy and the State Board's Resolution 68-16 (State Water Resources Control Board, Water Quality Order 86-17, p. 20 (1986) ("Order 86-17"); Memorandum from Chief Counsel William Attwater, SWRCB to Regional Board Executive Officers, "federal Antidegradation Policy," pp. 2, 18 (Oct. 7, 1987) ("State Antidegradation Guidance")). As a state policy, with inclusion in the Water Quality Control Plan (Basin Plan), the antidegradation policy is binding on all of the Regional Boards (Water Quality Order 86-17, pp. 17-18).

Implementation of the state's antidegradation policy is guided by the State Antidegradation Guidance, SWRCB Administrative Procedures Update 90-004, 2 July 1990 ("APU 90-004") and USEPA Region IX, "Guidance on Implementing the Antidegradation Provisions of 40 CFR 131.12" (3 June 1987) ("Region IX Guidance"), as well as Water Quality Order 86-17.

The Regional Board must apply the antidegradation policy whenever it takes an action that will lower water quality (State Antidegradation Guidance, pp. 3, 5, 18, and Region IX Guidance, p. 1). Application of the policy does not depend on whether the action will actually impair beneficial uses (State Antidegradation Guidance, p. 6). Actions that trigger use of the antidegradation policy include issuance, re-issuance, and modification of NPDES and Section 404 permits and waste discharge requirements, waiver of waste discharge requirements, issuance of variances, relocation of discharges, issuance of cleanup and abatement orders, increases in discharges due to industrial production and/or municipal growth and/or other sources, exceptions from otherwise applicable water quality objectives, etc. (State Antidegradation Guidance, pp. 7-10, Region IX Guidance, pp. 2-3). Both the state and federal policies apply to point and nonpoint source pollution (State Antidegradation Guidance p. 6, Region IX Guidance, p. 4).

The State Board's APU 90-004 specifies guidance to the Regional Boards for implementing the state and federal antidegradation policies and guidance. The guidance establishes a two-tiered process for addressing these policies and sets forth two levels of analysis: a simple analysis and a complete analysis. A simple analysis may be employed where a Regional Board determines that: 1) a reduction in water quality will be spatially localized or limited with respect to the waterbody, e.g. confined to the mixing zone; 2) a reduction in water quality is temporally limited; 3) a proposed action will produce minor effects which will not result in a significant reduction of water quality; and 4) a proposed activity has been approved in a General Plan and has been adequately subjected to the environmental and economic analysis required in an EIR. A complete antidegradation analysis is required if discharges would result in: 1) a substantial increase in mass

emissions of a constituent; or 2) significant mortality, growth impairment, or reproductive impairment of resident species. Regional Boards are advised to apply stricter scrutiny to non-threshold constituents, i.e., carcinogens and other constituents that are deemed to present a risk of source magnitude at all non-zero concentrations. If a Regional Board cannot find that the above determinations can be reached, a complete analysis is required.

Even a minimal antidegradation analysis would require an examination of: 1) existing applicable water quality standards; 2) ambient conditions in receiving waters compared to standards; 3) incremental changes in constituent loading, both concentration and mass; 4) treatability; 5) best practicable treatment and control (BPTC); 6) comparison of the proposed increased loadings relative to other sources; 7) an assessment of the significance of changes in ambient water quality and 8) whether the waterbody was a ONRW. A minimal antidegradation analysis must also analyze whether: 1) such degradation is consistent with the maximum benefit to the people of the state; 2) the activity is necessary to accommodate important economic or social development in the area; 3) the highest statutory and regulatory requirements and best management practices for pollution control are achieved; and 4) resulting water quality is adequate to protect and maintain existing beneficial uses. A BPTC technology analysis must be done on an individual constituent basis; while tertiary treatment may provide BPTC for pathogens, dissolved metals may simply pass through.

Any antidegradation analysis must comport with implementation requirements in State Board Water Quality Order 86-17, State Antidegradation Guidance, APU 90-004 and Region IX Guidance. The conclusory, unsupported, undocumented statements in the Permit are no substitute for a defensible antidegradation analysis.

There is nothing resembling an economic or socioeconomic analysis in the Permit. There are viable alternatives that have never been analyzed. The evaluation contains no comparative costs. As a rule-of-thumb, USEPA recommends that the cost of compliance should not be considered excessive until it consumes more than 2% of disposable household income in the region. This threshold is meant to suggest more of a floor than a ceiling when evaluating economic impact. In the Water Quality Standards Handbook, USEPA interprets the phrase “necessary to accommodate important economic or social development” with the phrase “substantial and widespread economic and social impact.”

The antidegradation analysis must discuss the relative economic burden as an aggregate impact across the entire region using macroeconomics. Considering the intrinsic value of the Delta to the entire state and the potential effects upon those who rely and use Delta waters, it must also evaluate the economic and social impacts to water supply, recreation, fisheries, etc. from the Discharger’s degradation of water quality in the Delta. Nor has the case been made that there is no alternative for necessary housing other than placing it where its wastewater must discharge directly into sensitive but seriously degraded waters. It is unfortunate that the agency charged with implementing the Clean Water Act has apparently decided it is more important to protect the polluter than the environment.

L. The Basin Plan, Implementation, Page IV-24-00, prohibits the discharge of wastewater to low flow streams as a permanent means of disposal and requires the evaluation of land disposal alternatives, Implementation, Page IV-15.00, Policies and Plans (2) Wastewater Reuse Policy.

The Basin Plan, Implementation, Page IV-24-00, Regional Water Board prohibitions, states that: “Water bodies for which the Regional Water Board has held that the direct discharge of waste is inappropriate as a permanent disposal method include sloughs and streams with intermittent flow or limited dilution capacity.” The Permit characterizes the receiving stream as low flow, or ephemeral, with no available dilution. The Permit does not discuss any efforts to eliminate the discharge to surface water and compliance with the Basin Plan Prohibition. Federal Regulation 40 CFR 122.4 states that no permit shall be issued for any discharge when the conditions of the permit do not provide for compliance with the applicable requirements of the CWA and are inconsistent with a plan or plan amendment. The permit must be amended to require that the Discharger develop a workplan to eliminate the wastewater discharge to surface water in accordance with the Basin Plan.

5. THE MANNER IN WHICH THE PETITIONERS ARE AGGRIEVED.

CSPA is a non-profit, environmental organization that has a direct interest in reducing pollution to the waters of the Central Valley. CSPA’s members benefit directly from the waters in the form of recreational hiking, photography, fishing, swimming, hunting, bird watching, boating, consumption of drinking water and scientific investigation. Additionally, these waters are an important resource for recreational and commercial fisheries.

Central Valley waterways also provide significant wildlife values important to the mission and purpose of the Petitioners. This wildlife value includes critical nesting and feeding grounds for resident water birds, essential habitat for endangered species and other plants and animals, nursery areas for fish and shellfish and their aquatic food organisms, and numerous city and county parks and open space areas.

CSPA’s members reside in communities whose economic prosperity depends, in part, upon the quality of water. CSPA has actively promoted the protection of fisheries and water quality throughout California before state and federal agencies, the State Legislature and Congress and regularly participates in administrative and judicial proceedings on behalf of its members to protect, enhance, and restore declining aquatic resources.

CSPA member’s health, interests and pocketbooks are directly harmed by the failure of the Regional Board to develop an effective and legally defensible program addressing discharges to waters of the state and nation.

6. THE SPECIFIC ACTION BY THE STATE OR REGIONAL BOARD WHICH PETITIONER REQUESTS.

Petitioners seek an Order by the State Board to:

- A. Vacate Order No. R5-2008-0162 (NPDES No. CA0084727) and remand to the Regional Board with instructions prepare and circulate a new tentative order that comports with regulatory requirements.
- B. Alternatively; prepare, circulate and issue a new order that is protective of identified beneficial uses and comports with regulatory requirements.

7. A STATEMENT OF POINTS AND AUTHORITIES IN SUPPORT OF LEGAL ISSUES RAISED IN THE PETITION.

CSPA's arguments and points of authority are adequately detailed in the above comments and our 16 September 2008 comment letter. Should the State Board have additional questions regarding the issues raised in this petition, CSPA will provide additional briefing on any such questions.

The petitioners believe that an evidentiary hearing before the State Board will not be necessary to resolve the issues raised in this petition. However, CSPA welcomes the opportunity to present oral argument and respond to any questions the State Board may have regarding this petition.

8. A STATEMENT THAT THE PETITION HAS BEEN SENT TO THE APPROPRIATE REGIONAL BOARD AND TO THE DISCHARGERS, IF NOT THE PETITIONER.

A true and correct copy of this petition, without attachment, was sent electronically and by First Class Mail to Ms. Pamela Creedon, Executive Officer, Regional Water Quality Control Board, Central Valley Region, 11020 Sun Center Drive #200, Rancho Cordova, CA 95670-6114.

A true and correct copy of this petition, without attachment, was sent to the Discharger in care of: Mr. Thomas L. Scesa, District Engineer, Tuolumne Utilities District, P.O. 3728, Sonora, CA 95370.

9. A STATEMENT THAT THE ISSUES RAISED IN THE PETITION WERE PRESENTED TO THE REGIONAL BOARD BEFORE THE REGIONAL BOARD ACTED, OR AN EXPLANATION OF WHY THE PETITIONER COULD NOT RAISE THOSE OBJECTIONS BEFORE THE REGIONAL BOARD.

CSPA presented the issues addressed in this petition to the Regional Board in a 16 September 2008 detailed comment letter that was accepted into the record.

If you have any questions regarding this petition, please contact Bill Jennings at (209) 464-5067 or Michael Jackson at (530) 283-1007.

Dated: 23 November 2008

Respectfully submitted,

A handwritten signature in black ink, appearing to read "Bill Jennings". The signature is written in a cursive, flowing style.

Bill Jennings, Executive Director
California Sportfishing Protection Alliance

Attachment No. 1: Order No. R5-2008-0162